

Appl. No. 10/541,258
 Amdt. Dated August 5, 2009
 Reply to Office action of June 1, 2006

RECEIVED
 CENTRAL FAX CENTER
 AUG 05 2009

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A liquid-spraying printing apparatus comprising:
 - a carrying means for carrying an object onto which liquid is to be projected ~~in a predetermined direction;~~
 - a liquid spraying means having nozzles to spray ~~and project~~ the liquid as droplets onto the object having been carried to a position where the object faces the nozzles;
 - a liquid-spraying controlling means for controlling the liquid spraying means to spray the droplets from the nozzles ~~in at a~~ at a predetermined timing;
 - an environment detecting means for detecting an ambient temperature and/or humidity when the droplets are sprayed from the nozzles;
 - a carrying-speed discriminating means for judging whether the carrying speed of the object has been changed ~~or not~~; and
 - a storage means having stored therein liquid-spraying control data intended for controlling the liquid-spraying timing ~~for each type of the object,~~
 - ~~when the carrying-speed discriminating means has determined that the object carrying speed has been changed,~~ the liquid-spraying controlling means controlling the liquid-spraying means when the carrying-speed discriminating means has determined that the object carrying speed has been changed to alter currently used liquid-spraying control data on the basis of the environment data detected by the environment detecting means and liquid-spraying control data

Appl. No. 10/541,258
Amdt. Dated August 5, 2009
Reply to Office action of June 1, 2008

~~stored in the storage means~~ to spray the droplets from the nozzles ~~in~~ at a different timing from that which is before the carrying speed is changed.

2. (Currently Amended) The printing apparatus according to claim 1, wherein:

the liquid spraying means has a plurality of the nozzles disposed side by side in the object-carrying direction to spray the droplets toward the object first from the upstream nozzle in the object-carrying direction and finally from the downstream one in this order in the object-carrying direction; and

~~the liquid spraying controlling means controls, taking a position to which the droplets sprayed from the nozzle located downstream in the object carrying direction as a reference droplet projected position, the liquid spraying to spray the droplets from the other nozzle than the nozzle located downstream in the different timing from that which is before the carrying speed is changed for the droplets sprayed from the other nozzle than the one located downstream to be projected to a generally same position as the reference droplet projected position before the nozzle located downstream sprays the droplets.~~

3. (Currently Amended) The printing apparatus according to claim 1, wherein

~~the carrying means is located upstream in the object carrying direction in relation to the liquid spraying means; and~~

the carrying means includes a feed roller that rotates about its own axis and a delivery roller located downstream in the object carrying direction in relation to the liquid spraying means to rotate which rotates about its own axis at a higher speed than the feed roller, ~~the feed and delivery rollers carrying nearly simultaneously the object having been carried to a position opposite to the nozzles to hold the object tight in a direction in the plane of the liquid spraying surface.~~

Appl. No. 10/541,258
Amdt. Dated August 5, 2009
Reply to Office action of June 1, 2006

4. (Currently Amended) The printing apparatus according to claim 1, wherein the carrying-speed discriminating means includes a trailing-end sensor located upstream of the liquid-spraying means in the object-carrying direction to detect the trailing end of the object in the carrying direction and which determines, ~~in a predetermined time after the trailing-end sensor has detected the trailing end of the object,~~ that the carrying speed has been changed.

5. (Currently Amended) The printing apparatus according to claim 1, wherein ~~of the liquid-spraying means,~~ the nozzles of the liquid-spraying means are disposed side by side generally in line in a direction generally perpendicular to the object-carrying direction.

6. (Currently Amended) A ~~liquid-spraying~~ printing method ~~to be employed in a liquid spraying apparatus~~ comprising:

~~a carrying means for carrying an object onto which liquid is to be projected in a predetermined direction~~ via a carrying mechanism;

~~a liquid spraying means having nozzles to spray and project the spraying liquid as droplets onto the object having been carried by a liquid spraying mechanism having nozzles to a position where the object faces the nozzles;~~

~~a liquid spraying controlling means for controlling the liquid spraying means to spray the droplets from the nozzles in predetermined timing~~ with a liquid spraying controlling mechanism;

~~an environment detecting means for detecting an ambient temperature and/or humidity when the droplets are sprayed from the nozzles~~ with an environment detecting mechanism;

~~a carrying speed discriminating means for judging whether the carrying speed of the object has been changed~~ with a carrying speed detecting mechanism ~~or not;~~ and

~~a storage means having stored therein~~ storing liquid-spraying control data intended for controlling the liquid-spraying timing ~~for each type of the object,~~

Appl. No. 10/541,258
Amdt. Dated August 5, 2009
Reply to Office action of June 1, 2006

~~whereby when the carrying speed discriminating means has determined that the object carrying speed has been changed, the droplets are sprayed~~ spraying droplets from the nozzles at a ~~in different timing when the carrying speed detecting mechanism determines that the carrying speed has changed based on from that which is before the carrying speed is changed on the basis of the environment data detected by the environment detecting mechanism means and liquid-spraying control data stored in the storage means.~~

7. (Currently Amended) The printing method according to claim 6, wherein:

a plurality of the nozzles ~~is~~ are disposed side by side in the object-carrying direction to spray the droplets toward the object first from an ~~the~~ upstream nozzle in the object-carrying direction and finally from a ~~the~~ downstream one in this order in the object-carrying direction; ~~and~~ ~~—— a position to which the droplets sprayed from the nozzle located downstream in the object-carrying direction being taken as a reference droplet projected position, the liquid spraying is controlled to spray the droplets from the other nozzle than the nozzle located downstream in the different timing from that which is before the carrying speed is changed for the droplets sprayed from the other nozzle than the one located downstream to be projected to a generally same position as the reference droplet projected position before the nozzle located downstream sprays the droplets.~~

8. (Currently Amended) The printing method according to claim 7, wherein as the carrying mechanism means, there are provided includes a feed roller located upstream of the liquid-spraying means in the object carrying direction that rotates ~~to rotate~~ about its own axis, and a delivery roller located downstream of the liquid-spraying means in the object carrying direction ~~to rotate~~ that rotates about its own axis at a higher speed than the feed roller; ~~the object having been carried to a position opposite to the nozzles being carried by the feed and~~

Appl. No. 10/541,258
Amdt. Dated August 5, 2009
Reply to Office action of June 1, 2006

~~delivery rollers almost simultaneously to hold the object tight in a direction in the plane of the liquid-spraying surface.~~

9. (Currently Amended) The printing method according to claim 6, wherein the carrying speed detecting mechanism ~~carrying-speed discriminating means~~ includes a trailing-end sensor located upstream of the liquid-spraying means in the object-carrying direction which detects to ~~detect~~ the trailing end of the object in the carrying direction and which determines, ~~in a predetermined time after the trailing-end sensor has detected the trailing end of the object,~~ that the carrying speed has been changed.

10. (Currently Amended) The printing method according to claim 6, wherein the nozzles are disposed side by side generally in line in a direction generally perpendicular to the object-carrying direction.

11. (Currently Amended) A ~~liquid-spraying apparatus~~ printing comprising:

a carrying means for carrying an object onto which liquid is to be projected in a predetermined direction;

a liquid spraying means having nozzles to spray ~~and project~~ the liquid as droplets onto the object having been carried to a position where the object faces the nozzles;

a liquid-spraying controlling means for controlling the liquid spraying means to spray the droplets from the nozzles at a ~~in~~ predetermined timing;

an environment detecting means for detecting an ambient temperature and/or humidity when the droplets are sprayed from the nozzles;

a carrying-speed discriminating means for judging whether the carrying speed of the object has been changed ~~or not~~;

a droplet-projected position detecting means for detecting a displacement of a droplet-

Appl. No. 10/541,258
 Amdt. Dated August 5, 2009
 Reply to Office action of June 1, 2006

projected position, which arises when the droplets are projected in a predetermined pattern on the object being carried because the object carrying speed has been changed;

a data generating means for generating, ~~for each type of the object onto which the droplets are projected in the predetermined pattern,~~ liquid-spraying control data intended for controlling the liquid-spraying timing to correct the displacement of droplet-projected position detected by the liquid-protected position detecting means; and

a storage means for storing the liquid-spraying control data generated by the data generating means ~~for each object type,~~

~~when the carrying speed discriminating means has determined that the object carrying speed has been changed,~~ the liquid-spraying controlling means controlling the liquid-spraying means when the carrying-speed discriminating means has determined that the object carrying speed has been changed on the basis of the environment data detected by the environment detecting means and liquid-spraying control data ~~for each object type,~~ stored in the storage means, to spray the droplets from the nozzles at a ~~in~~ different timing from that which is before the carrying speed is changed.

12. (Currently Amended) The printing apparatus according to claim 11, wherein

the liquid spraying means has a plurality of the nozzles disposed side by side in the object-carrying direction to spray the droplets toward the object first from the upstream nozzle in the object-carrying direction and finally from the downstream one in this order in the object-carrying direction;

~~the droplet projected position detecting means detects, taking a position to which the droplets sprayed from the nozzle located downstream in the object-carrying direction are projected as a reference droplet projected position, a displacement of the position to which the~~

Appl. No. 10/541,258
Amdt. Dated August 5, 2009
Reply to Office action of June 1, 2006

~~droplets sprayed from the other nozzle than the one located downstream are projected from the reference droplet projected position; and~~

~~the data generating means generates the liquid spraying control data intended for controlling the timing of liquid spraying from the other nozzle than the one located downstream so that the droplets sprayed from the other nozzle than the one located downstream will be projected to the generally same position as the reference droplet projected position before the nozzle located downstream sprays the droplets.~~

13. (Currently Amended) The printing apparatus according to claim 11, wherein:

~~the carrying means is located upstream in the object carrying direction in relation to the liquid spraying means; and~~

~~the carrying means includes a feed roller that rotates about its own axis and a delivery roller located downstream in the object carrying direction in relation to the liquid spraying means which rotates to rotate about its own axis at a higher speed than the feed roller, the feed and delivery rollers carrying nearly simultaneously the object having been carried to a position opposite to the nozzles to hold the object tight in a direction in a direction in the plane of the liquid spraying surface.~~

14. (Currently Amended) The printing apparatus according to claim 11, wherein the carrying-speed discriminating means includes a trailing-end sensor provided upstream in the object-carrying direction in relation to the liquid-spraying means to detect the trailing end of the object in the carrying direction and which determines, in a predetermined time after the trailing end sensor has detected the trailing end of the object, that the carrying speed has been changed.

15. (Currently Amended) The printing apparatus according to claim 11, wherein the storage means has pre-stored therein the liquid-spraying control data for the type of the object.

Appl. No. 10/541,258
Amdt. Dated August 5, 2009
Reply to Office action of June 1, 2006

16. (Currently Amended) The printing apparatus according to claim 11, wherein ~~of the liquid-spraying means~~, the nozzles of the liquid-spraying means are disposed side by side generally in line in a direction generally perpendicular to the object-carrying direction.

17. (Currently Amended) A printing liquid-spraying method ~~for to be employed in a liquid spraying apparatus~~ comprising:

~~a carrying means for carrying an object onto which liquid is to be projected in a predetermined direction~~ with a carrying mechanism;

~~a liquid-spraying means having nozzles to spray and project~~ spraying the liquid as droplets onto the object having been carried to a position where the object faces the nozzles with a liquid spraying mechanism;

~~a liquid-spraying controlling means for controlling the liquid spraying mechanism~~ means to spray the droplets from the nozzles at a in predetermined timing;

~~an environment detecting means for detecting an ambient temperature and/or humidity when the droplets are sprayed from the nozzles~~ with an environment detecting apparatus;

~~a carrying speed discriminating means for judging whether the carrying speed of the object has been changed~~ with a carrying speed discriminating mechanism or not;

~~a droplet-projected position detecting means for detecting a displacement of droplet-projected position, which arises when the droplets are projected in a predetermined pattern on the object being carried because the object carrying speed has been changed~~ with a droplet projected position detecting mechanism;

~~a data-generating means for generating, for each type of the object on which the droplets are projected in the predetermined pattern, liquid-spraying control data intended for controlling~~

Appl. No. 10/541,258
 Amdt. Dated August 5, 2009
 Reply to Office action of June 1, 2006

the liquid-spraying timing to correct the displacement of droplet-projected position detected by the liquid-protected position detecting mechanism means; and

~~a storage means for storing the liquid-spraying control data generated by the data generating means for each object type;~~

whereby when the carrying-speed discriminating mechanism means has determined that the object carrying speed has been changed, the liquid-spraying controlling mechanism means controls the liquid-spraying mechanism means on the basis of the environment data detected by the environment detecting mechanism means and liquid-spraying control data ~~for each object type, stored in the storage means,~~ to spray the droplets from the nozzles at a in different timing from that which is before the carrying speed is changed.

18. (Currently Amended) The printing method according to claim 17, wherein:

a plurality of the nozzles ~~is~~ are disposed side by side in the object-carrying direction to spray the droplets toward the object first from the upstream nozzle in the object-carrying direction and finally from the downstream one in this order in the object-carrying direction;

~~a position to which the droplets sprayed from the nozzle located downstream in the object-carrying direction are projected being taken as a reference droplet projected position, a displacement of the position to which the droplets sprayed from the other nozzle than the one located downstream are projected from the reference droplet projected position is detected by the droplet projected position detecting means; and~~

~~the liquid spraying control data, intended for controlling the timing of liquid spraying from the other nozzle than the one located downstream so that the droplets sprayed from the other nozzle than the one located downstream will be projected to the generally same position as the reference droplet projected position before the nozzle located downstream sprays the droplets, is~~

Appl. No. 10/541,258
Amdt. Dated August 5, 2009
Reply to Office action of June 1, 2006

~~generated by the data-generating means.~~

19. (Currently Amended) The printing method according to claim 17, wherein as the carrying ~~mechanism means~~, there are provided a feed roller located upstream of the liquid-spraying means in the object carrying direction ~~to rotate about its own axis~~, and a delivery roller located downstream of the liquid-spraying means in the object carrying direction which rotates ~~to rotate~~ about its own axis at a higher speed than the feed roller, ~~the object having been carried to a position opposite to the nozzles being carried by the feed and delivery rollers almost simultaneously to hold the object tight in a direction in the plane of the liquid-spraying surface.~~

20. (Currently Amended) The printing method according to claim 17, wherein the carrying-speed discriminating ~~mechanism means~~ includes a trailing-end sensor located upstream of the liquid-spraying means in the object-carrying direction to detect the trailing end of the object in the carrying direction and which determines, ~~in a predetermined time after the trailing-end sensor has detected the trailing end of the object,~~ that the carrying speed has been changed.

21. (Currently Amended) The printing method according to claim 17, wherein the liquid-spraying control data ~~for the type of the object is pre-stored in the storage means.~~

22. (Currently Amended) The printing method according to claim 17, wherein the nozzles are disposed side by side generally in line in a direction generally perpendicular to the object-carrying direction.